

Patent Abstracts of Japan

PUBLICATION NUMBER : 61110652  
PUBLICATION DATE : 28-05-86



APPLICATION DATE : 05-11-84  
APPLICATION NUMBER : 59233848

APPLICANT : NIPPON DENSO CO LTD;

INVENTOR : HONDA YUKIO;

INT.CL. : B60S 1/38

TITLE : WIPER BLADE RUBBER



X → 1, 2, 7

ABSTRACT : PURPOSE: To aim at preventing the occurrence of a noise, by setting up intermediate rubber between a lip part wiping a windshield surface and a rubber upper part, while installing a neck part at more than two spots, and making the lip part optionally tilt to the windshield plane surface with flexibility inherent in these two neck parts.

CONSTITUTION: In the conventional rubber, since there is no intermediate rubber, a rubber wiping part 5 is tilted down at a stroke at a turnover position as far as a portion for the angle  $\alpha$  till rubber shoulder parts 9 and 10 hit a metal fitting keeping part 1 whereby the impact force required for the turnover is large enough, emitting a noise there. Accordingly, first, the intermediate rubber 18 tilts down as far as an angle  $\beta$  till shoulder parts 7 and 8 hit the metal fitting keeping part 1 and afterward a lip part 5 tilts down as far as a portion for an angle  $\gamma$  till these shoulder parts 9 and 10 hit the intermediate rubber 18 whereby the impact force in time of turning over is made dispersible. Thus, noises and vibrations due to the turnover are sharply reducible.

COPYRIGHT: (C)1986,JPO&Japio